Also published as:

US2002026567 (A1)

MICRO PROCESSOR

Publication number: JP2002073418 (A)

Publication date:

2002-03-12

Inventor(s):

NAITO MUTSUHIRO; MIZOGUCHI KAZUAKI

Applicant(s):

FUJITSU LTD

Classification:

- international:

G06F12/14; G06F12/00; G06F15/78; G06F21/24;

G06F12/14; G06F12/00; G06F15/76; G06F21/00;

(IPC1-7): G06F12/14; G06F15/78

- European:


G06F12/14C1B

Application number: JP20000255318 20000825 **Priority number(s):** JP20000255318 20000825

Abstract of JP 2002073418 (A)

PROBLEM TO BE SOLVED: To provide a low end microprocessor with additional simple hardware that allows an access to a memory and also prohibits the access to the memory. SOLUTION: The low end microprocessor 10 has a stack pointer 18, a comparator 17 that compares the pointer contents of SPV with a specified value ADR 1, an inverter 19 that inverts CP as the result of the comparison, and an AND gate 16 that is fed by a write request signal WR from a CPU 11 and an output of the inverter 19. The microprocessor feeds the output of the AND gate 16 into a write enable signal input terminal WE of a memory 12 that can permit or prohibit write operations on a basis of the depth of the stack.

ボ空明の第1連島が能のマイジョブロセッサの 関語プログス図



Data supplied from the esp@cenet database — Worldwide